Flexi™ ceiling panel and cloud

Fabric wrapped panel for ceilings, flush fixed or suspended as a cloud



Sizes	1200 × 600 mm (standard) · Custom sizes on request
Thickness	50 mm
Acoustic	NRC 1.00 at 50 mm (ASTM C423, mounting A). Suspended clouds absorb on both faces
Core	As the wall panel: 96 kg/m³ glass fibre core, resin-hardened edges
Face	Acoustically transparent polyester fabric, 39 standard colours
Edges	Bevel edged (standard) or straight edged
Weight	About 4 kg per 1200 × 600 panel, about 10 N per fixing point on four points
Fixing	Suspended about 100 mm below the soffit on four spring and wire sets, or fixed flush with helical anchors; hook-on to sloped ceilings
Typical use	Open offices, restaurants, studios, pilates and dance studios, halls
Colours	39 standard Flexi™ fabric colours; physical swatch card on request
Fire and emissions	Flexi™ core: EN 13501-1 Class A1 (membrane components), formaldehyde not detected, asbestos negative (SGS XMIN180901795CCM). Fabric: UK FFR 1988 Sch. 4/5 Part I pass (SGS SDHL1803005038FB)
Lead time	About 15 working days on our production schedule after the deposit, then delivery; about 4 to 6 weeks to installed
Warranty	1 year on materials and workmanship
Care	Vacuum gently or wipe lightly with a dry or slightly damp cloth. Do not soak or scrub